

フィルター



H1G513G1 /H2G513G2



N0321401

Part Number: H1G513G1

Parameter	Specification
Component Type:	High Pass
Description:	Highpass Filter
Pass Band:	1500 - 13000 MHz
Insertion Loss:	< 1.5 dB
VSWR:	< 2 :1
Impedance:	50 Ohms
Rejection Lower Limit:	> 40 dBc from DC to 1000 MHz
Continuous RF Power:	1.00 W
Operating Temperature:	- 54 C to + 85 C
Mounting:	Tapped Holes in Body
Connectors:	SMA Female/Female
Finish:	White Epoxy Paint per MIL-PRF-22750F
Weight:	0.7 Ounces nominal
Height:	0.38 "
Width:	0.38 "
Length:	1.25 "
Package Type:	Connectorized
* NOTE: Length dimensions excludes connectors, RF pins and tabs.	

Part Number: H2G513G2

Parameter	Specification
Component Type:	High Pass
Description:	Highpass Filter, Microwave Miniature
Pass Band:	2500 - 12750 MHz
Insertion Loss:	< 1.5 dB
VSWR:	< 2.0 :1
Impedance:	50 Ohms
Rejection Lower Limit:	> 50 dBc from DC to 2000 MHz
Continuous RF Power:	2.00 W
Operating Temperature:	- 30 C to + 60 C
Mounting:	Tapped Holes in Body
Connectors:	SMA Female/Female
Finish:	White Epoxy Paint per MIL-PRF-22750F
Weight:	1.7 Ounces
Height:	0.50 "
Width:	0.50 "
Length:	1.50 "
Package Type:	Connectorized
* NOTE: Length dimensions excludes connectors, RF pins and tabs.	

Part Number: N0321401

Parameter	Specification
Component Type:	Notch
Center Frequency:	2160 MHz
Lower Passband:	DC - 1920 MHz
Upper Passband:	2400 - 13000 MHz
Insertion Loss:	< 1.0 dB
VSWR:	< 2.0 :1
Impedance:	50 Ohms
Rejection Center:	2140 MHz
Rejection:	70 dB @ 2110 - 2170 MHz
Peak RF Power:	1 W
Operating Temperature:	- 40 C to + 70 C
Mounting:	Tapped Holes in Body
Connectors:	SMA Female/Female
Finish:	White Epoxy Paint per MIL-PRF-22750F
Weight:	6.4
Height:	0.50 "
Width:	0.75 "
Length:	4.00 "
Package Type:	Connectorized
* NOTE: Length dimensions excludes connectors, RF pins and tabs.	